

S.T.E.P™ GLS

Product Description:

Special Torque-resistant Edging Pad, Green Lens Side

This PE foam pad features a unique internal reinforcement to prevent stretching and thus reduce axis problems. Moreover it is provided with two different adhesives.

One side (dark green color) has a special engineered adhesive that attaches to Super Hydrophobic coatings and the other side (black color) has an adhesive specially for the block side. Both adhesives are clean removable.

Directions for use:

Exclusively for use on lenses that have Super-Hydrophobic or Oleophobic coatings. The patented adhesive is compatible only with such coatings; use on lenses without an SH coating will result in poor performance and may

Physical Properties:

Adhesive	Patented adhesive technology
Carrier	High density reinforced closed cell polyolefine foam
Total thickness	1.0 mm
Liner Manual roll	White Glassine Paper and PET
Liner Machine roll	PE and PET
Temperature resistance	-40°C - +90°C
Shelf Life	12 months from dispatch when stored in original cartons at 21°C and under 50% relative humidity

The data and details in this sheet were correct and up-to-date at the time of printing and are intended to provide information on our products and their possible applications. This sheet is not a specification and does not assure specific product characteristics or make reference to the suitability of the products for a definite application. Because Permanento cannot anticipate or control every application, we strongly recommend testing of this product under individual application conditions. In accordance with our policy of continuous improvement specifications may vary.



Permanento Edge-It B.V
Oeverkruid 2
4941 VV Raamsdonksveeer
Netherlands
Phone: +31 (0) 162 58 9400
sales@permanento.com