

Xpad I

Product Description:

This Lens Edging Application Pad has a specially engineered very strong high density PE foam carrier which has the highest axis torsion resistance ever.

The unique specially engineered hybrid adhesive will prevent slippage as never before. That is why Xpad I is usable on all standard coated and almost on any hard to bond Super and Ultra Hydrophobic lenses.

It is even usable on hard to stick lenses from Asian companies. Top paper liner prevents annoying static charge.

Directions for use:

- Lens side is indicated by a gold pull tab.
- Block side is indicated by a red pull tab.

This pad is suitable for almost any lens, except uncoated lenses.

Physical Properties:

Adhesive	Very aggressive hybrid adhesive
Carrier	Conformable closed cell PE foam
Total thickness	0.9 mm
Liner Manual roll	Top, white glassine printed paper Bottom, white glassine unprinted paper
Liner Machine roll	Top, translucent blue PE film. Bottom, transparent PET film.
Temperature resistance	Up to +80°C
Shelf Life	12 months from dispatch when stored in original cartons at 21°C and under 50% relative humidity

The data and details in this sheet were correct and up-to-date at the time of printing and are intended to provide information on our products and their possible applications. This sheet is not a specification and does not assure specific product characteristics or make reference to the suitability of the products for a definite application. Because Permanento cannot anticipate or control every application, we strongly recommend testing of this product under individual application conditions. In accordance with our policy of continuous improvement specifications may vary.



Permanento Edge-It B.V
Oeverkruid 2
4941 VV Raamsdonksveeer
Netherlands
Phone: +31 (0) 162 58 9400
sales@permanento.com