

# DATA SHEET

## S.T.E.P™ II

### Product Description:

S.T.E.P. II, is our improved successor of our bestseller S.T.E.P. **Special Torque-resistant Edging Pad**. This Lens Edging Pad features an improved internal reinforcement that prevents stretching and thus reduces axis problems. With its new high-tack acrylic adhesive, S.T.E.P. II is suitable for all kinds of lenses.

With our double tapped fingerlift technology this premium product allows an easy removal of the lens edging pad in one clean piece. The new developed high-tack adhesive ensures a secure hold during the edging process, resulting in precise and accurate Edging proces every time.

Whether you're working with standard, high-index, or polarized lenses, S.T.E.P. II offers superior torque-resistance and accuracy. Upgrade your lab's lens edging process with S.T.E.P. II and experience the lasting benefits of a premium product.

### Directions for use:

Before use, make sure lens and block are free of moist, dust and grease.

### Physical Properties:

Adhesive	High tack Acrylic adhesive
Carrier	Reinforced closed cell PE foam 0,91mm (+/- 15%)
Total thickness	0,91 mm
Liner Manual roll	Top, printed glassine paper Bottom, white glassine paper
Liner Machine roll	Top, translucent blue PE film Bottom, transparent PET film
Temperature resistance	-40°C up to 100°C
Shelf Life	12 months from dispatch when stored in original cartons between 10°C to 35°C and under 50% relative humidity

**All standard shapes are available, and custom shapes can be provided upon request. Please visit our website for a list of standard shapes.**

Data and detail in this sheet were correct and up-to-date at the time of printing and are intended to provide information on our products and their possible applications. This sheet is not a specification and does not assure specific product characteristics or make reference to the suitability of the products for a definite application. Because Permanento cannot anticipate or control every application, we strongly recommend testing of this product under individual application conditions. In according with our policy of continuous improvement specifications may vary.



Permanento Edge-It B.V.  
Oeverkruid 2 4941 VV Raamsdonksveer  
Netherlands  
Phone: +31 (0) 162 58 9400  
[sales@permanento.com](mailto:sales@permanento.com)