DATA SHEET

STEP[™] GLS+

Product Description:

Special Torque-resistant Edging Pad, Green Lens Side+

This blocking pad is especially designed for Superhydrophobic lenses of the latest generation.

This PE foam pad features a unique internal reinforcement to prevent stretching and thus reduce axis problems. Moreover it is provided with two different adhesives. One side (dark green colour) has a special engineered adhesive that attaches to Super Hydrophobic coatings and the other side (black colour) has an adhesive specially for the block side. Both adhesives are clean removable.

Step GLS+ is easy to use and can be used with any lens edging machine and is available for fully automatic as manual edgers.

Directions for use:

Before use, make sure lens and block are free of moist, dust and grease.

- Lens side is dark green-coloured
- Block side is black-coloured

Note: This pad is only suitable for Super Hydrophobic or Oleophobic lenses

Physical Proporties:

Adhesive:	Patented adhesive technology
Carrier:	High conformable reinforced closed cell PE foam
Total thickness:	0,94 mm +/- 15%
Liner Manual roll:	Top, PET film Bottom, White Glassine Paper
Liner Machine roll:	Top, PE Bottom, PET film
Temperature resistand	ce: -40°C - +100°C
Shelf Life:	12 months from dispatch when stored in original cartons between 10°C and 35°C and under 50% relative humidity

All standard shapes are available, and custom shapes can be provided upon request. Please visit our website for a list of standard shapes.

Data and detail in this sheet were correct and up-to-date at the time of printing and are intended to provide information on our products and their possible applications. This sheet is not a specification and does not assure specific product characteristics or make reference to the suitability of the products for a definite application. Because Permanento cannot anticipate or control every application, we strongly recommend testing of this product under individual application conditions. In according with our policy of continuous improvement specifications may vary.





Permanento Edge-It B.V Oeverkruid 2 4941 VV Raamsdonksveer Netherlands Phone: +31 (0) 162 58 9400 sales@permanento.com